

**Listing of Claims:**

1           1.       (Currently Amended) A movable support system adapted for providing at  
2       least one display device within a work space having a floor and configured for use by at least  
3       one user comprising:

4                   a mounting structure;

5                   a track system mounted to the mounting structure and providing a track;

6                   a display support assembly having a first section movably coupled to the track  
7       and a second section projecting beyond the track into the work space and configured for  
8       attachment of at least one display device;

9                   a work surface mounted to the mounting structure above the first section of the  
10       display support assembly to provide a slot through which the second section of the display  
11       support assembly projects into the work space;

12                  wherein at least one display device installed on the display support assembly  
13       may be selectively positioned for use within the work space in a variety of positions by (a)  
14       movement of the display support assembly relative to the mounting structure within the slot  
15       and transverse to the work surface and (b) movement of the display device relative to the  
16       display support assembly; and

17                  wherein the second section of the display support assembly is cantilevered a  
18       sufficient distance away from the mounting structure so that clearance is provided between  
19       the display support assembly and the floor of the work space and so that display device may  
20       be used in a plurality of positions including (a) a first position where the display device faces  
21       toward the track system, (b) a second position where the display device is transverse to the  
22       track system, and (c) a third position where the display device faces away from the track  
23       system.

1           2.       (Original) The system of Claim 1 wherein the track is linear.

1           3.       (Original) The system of Claim 1 wherein the track is coupled to an article of  
2       furniture.

1           4.       (Original) The system of Claim 1 wherein the track is mounted on storage  
2 furniture.

1           5.       (Canceled)

1           6.       (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly provides a plurality of arms.

1           7.       (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly is configured to provide at least one passage for management of one or more cables  
3 coupled to the display device.

1           8.       (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly includes a hub providing for management of one or more cables coupled to the  
3 display device.

1           9.       (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly is configured for coupling of two display devices.

1           10.      (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly includes a pair of flanges and a pair of arms and a display device is attachable to  
3 each of the pair of arms.

1           11.      (Previously Presented) The system of Claim 1 further comprising at least one  
2 display device coupled to the display support assembly.

1           12.      (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly is cantilevered from the track.

1           13.      (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly is perpendicular to the track.

1           14.      (Previously Presented) The system of Claim 1 wherein the display support  
2 assembly is non-pivotably mounted to the track.

1           15.     (Previously Presented) The system of Claim 1 configured for use in a work  
2     space providing at least one mobile table and wherein the display support assembly is at a  
3     height above the mobile table.

1           16.     (Previously Presented) The system of Claim 1 wherein the display support  
2     assembly is configured for at least two display panels.

1           17.     (Original) The system of Claim 8 wherein the management of one or more  
2     cables is provided at least partially through one or more passages.

1           18.     (Currently Amended) An apparatus providing a movable support system  
2 adapted for providing a display device configured to provide at least two display panels  
3 within a work space having a floor and configured for use by at least one user comprising:  
4                 a mounting structure;  
5                 a track system mounted to the mounting structure and providing at least one  
6 track;  
7                 a display support assembly having a first section movably coupled to the track  
8 and a second section projecting beyond the track into the work space and configured for  
9 attachment to at least two display panels;  
10                a worksurface mounted to the mounting structure above the first section of the  
11 display support assembly to provide a gap through which the second section of the display  
12 support assembly projects into the work space;  
13                wherein each of the display panels is coupled to the second section of the  
14 display support assembly by an arm providing a first joint and a second joint; and  
15                wherein each of the display panels may be selectively positioned for use within  
16 the work space in a variety of positions by (a) movement of the display support assembly  
17 relative to the mounting structure within the gap and transverse to the work surface and (b)  
18 movement of the display panels relative to the display support assembly about the arm; and  
19                wherein the second section of the display support assembly is cantilevered a  
20 sufficient distance away from the mounting structure so that clearance is provided between  
21 the display support assembly and the floor of the work space and so that each of the display  
22 panels may be used in a plurality of positions including (a) a first position where the display  
23 panels face toward the track system, (b) a second position where the display panels are  
24 transverse to the track system, and (c) a third position where the display panels face away  
25 from the track system.

1           19.     (Original) The apparatus of Claim 18 wherein the track system is a linear  
2 track.

1           20.     (Original) The apparatus of Claim 18 wherein the track is mounted to an  
2 article of furniture.

1           21.     (Original) The apparatus of Claim 18 wherein the track is mounted on storage  
2 furniture.

1           22     (Previously Presented) The apparatus of Claim 18 wherein the work surface is  
2 mounted over the track.

1           23.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly has at least two articulable arms.

1           24.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 is configured to provide a passage for management of wires.

1           25.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly manages wires through a hub.

1           26.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly is pivotably coupled to the display support assembly at a hub.

1           27.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly provides at least two flanges each for attachment of at least one articulable arm  
3 attachable to at least one display device.

1           28.     (Previously Presented) The apparatus of Claim 18 further comprising at least  
2 one display device coupled to the display support assembly.

1           29.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly is cantilevered from the track.

1           30.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly is perpendicular to the track.

1           31.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly is non-pivotably mounted to track.

1           32.     (Previously Presented) The apparatus of Claim 18 configured for use in a  
2 work space providing at least one mobile table and wherein the display support assembly is at  
3 a height above the mobile table.

1           33.     (Previously Presented) The apparatus of Claim 18 wherein the display support  
2 assembly is configured to provide at least one passage for management of at least one cable  
3 coupled to the display device.

1           34.     (Currently Amended) A movable support system adapted for providing at  
2     least one display device within a work space having a floor and configured to be coupled to  
3     utilities such as power or data through cables, comprising:  
4                 a mounting structure;  
5                 a track system mounted to the mounting structure and providing a track;  
6                 a display support assembly having a first section movably coupled to the track  
7     and a second section cantilevered away from the mounting structure and projecting beyond  
8     the track into the work space and configured for attachment of the display device so that a  
9     clearance is provided between the display support assembly and the floor of the work space  
10    and so that the display device may be used in a plurality of positions including (a) a first  
11    position where the display device faces toward the track system, (b) a second position where  
12    the display device is transverse to the track system, and (c) a third position where the display  
13    device faces away from the track system;  
14                 a worksurface mounted to the mounting structure above the first section of the  
15    display support assembly to provide a gap through which the second section of the display  
16    support assembly projects into the work space;  
17                 wherein the display device installed on the display support assembly may be  
18    selectively positioned for use within the work space in a variety of positions relative to the  
19    track by (a) movement of the display support assembly relative to the mounting structure  
20    within the gap and transverse to the work surface and (b) movement of the display device  
21    relative to the display support assembly; and  
22                 wherein the display support assembly is configured to provide at least one  
23    passage for management of cables configured to be coupled to the display device.

1           35.     (Original) The system of Claim 34 wherein the track is linear.

1           36.     (Original) The system of Claim 34 wherein the track is coupled to an article of  
2     furniture.

1           37.     (Original) The system of Claim 34 wherein the track is mounted on storage  
2     furniture.

1           38.     (Canceled)

1           39.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly provides a plurality of arms.

1           40.     (Previously Presented) The system of Claim 51 wherein the display support  
2 assembly is configured to provide at least one passage for management of a cable coupled to  
3 the display device.

1           41.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly includes a hub providing for management of one or more cables coupled to the  
3 display device.

1           42.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly is configured for coupling of two display devices.

1           43.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly includes a pair of flanges and a pair of arms and a display device is attachable to  
3 each of the pair of arms.

1           44.     (Previously Presented) The system of Claim 34 further comprising at least one  
2 display device coupled to the display support assembly.

1           45.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly is cantilevered from the track.

1           46.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly is perpendicular to the track.

1           47.     (Previously Presented) The system of Claim 34 wherein the display support  
2 assembly is non-pivotably mounted to track.



1           48.     (Previously Presented) The system of Claim 34 configured for use in a work  
2     space providing at least one mobile table and wherein the display support assembly is at a  
3     height above the mobile table.

1           49.     (Previously Presented) The system of Claim 34 wherein the display support  
2     assembly is configured for at least two display panels.

1           50.     (Previously Presented) The system of Claim 34 wherein the management of  
2     cables is provided at least partially through passages in the display support assembly.

1           51.     (Currently Amended) A movable support system adapted for providing at  
2     least one display device configured for use by at least one person in a work space having a  
3     floor and an entrance, comprising  
4                 a mounting structure;  
5                 a track system mounted to the mounting structure and providing a track;  
6                 a display support assembly having a first section movably coupled to the track  
7     and a second section projecting beyond the track into the work space and configured for  
8     attachment of at least one display device;  
9                 wherein a display device installed on the display support assembly may be  
10    selectively positioned for use within the work space in a variety of positions by (a) movement  
11    of the display support assembly relative to the mounting structure transverse to the work  
12    surface and (b) movement of the display device relative to the display support assembly about  
13    at least one of a first joint, a second joint and a third joint; ~~and~~  
14                 wherein the second section of the display support assembly is cantilevered a  
15    sufficient distance away from the mounting structure so that clearance is provided between  
16    the display support assembly and the floor of the work space so that the display device may  
17    be used in a plurality of positions including (a) a first position where the display device faces  
18    toward the track system, (b) a second position where the display device is transverse to the  
19    track system, and (c) a third position where the display device faces away from the track  
20    system; and  
21                 so that each person within the work space may selectively choose a body  
22    orientation or a body position relative to the entrance or otherwise within the workspace  
23    while using the display device.

1           52.     (Previously Presented) The system of Claim 51 wherein a range of motion  
2     provided by the display support assembly is such that the body orientation or body position of  
3     at least one person using the display device in the work space relative to the entrance may  
4     include (a) back to the entrance; (b) face to the entrance; or (c) profile or side to the entrance.

1           53.     (Previously Presented) The system of Claim 51 wherein a position of the  
2 person relative to the display device can be adapted from a first position where information  
3 contained on the display device is not perceptible to the person to a second position where  
4 information contained on the display device is perceptible to the person by relative movement  
5 of the display support assembly and without requiring that the person make substantial  
6 change in body orientation or body position.

1           54.     (Previously Presented) The system of Claim 51 wherein one or both of two  
2 users can adapt the position of at least one display device to improve the viewing position for  
3 perception of information on the display device by movement of the display support  
4 assembly.

1           55.     (Previously Presented) The system of Claim 51 wherein the display device  
2 can be moved using the display support assembly from a non-use position where information  
3 contained on the display device is not perceptible to the person to an in-use position where  
4 information contained on the display device is perceptible to the person.

1           56.     (Original) The system of Claim 51 wherein the display device is configured  
2 for use by a plurality of users including a first group of at least one person and a second group  
3 of at least one person and for movement between a first position and a second position so that  
4 in the first position information contained on the display device is perceptible to the first  
5 group and in the second position information contained on the display device is perceptible to  
6 the second group, the information being private or concealed to the second group of users in  
7 the first position and public or visible to the second group of users in the second position.

1           57.     (Previously Presented) The apparatus of Claim 18 wherein the first joint  
2 comprises a pivotable joint between the display support assembly and the display device to  
3 facilitate movement of the display device about a first axis and the second joint comprises a  
4 pivotable joint between the display support assembly and the display device to facilitate  
5 movement of the display device about a second axis so that the display device is selectively  
6 repositionable relative to the support in at least one of upwardly, downwardly, laterally and  
7 pivotably.

1           58.     (Previously Presented) The apparatus of Claim 51 wherein the first joint  
2 comprises a pivotable joint between the second section of the display support assembly and  
3 the display device to facilitate pivotal movement of the display device about a first axis and  
4 the second joint comprises a pivotable joint between the second section of the display support  
5 assembly and the display device to facilitate pivotal movement of the display device about a  
6 second axis and the third joint comprises a pivotable joint between the second section of the  
7 display support assembly and the display device to facilitate pivotal movement of the display  
8 device about a third axis so that the display device is selectively repositionable relative to the  
9 display support assembly in at least one of upwardly, downwardly, laterally and pivotably.

1           59.     (Previously Presented) The apparatus of Claim 57 wherein the first axis is a  
2 vertical axis and the second axis is a horizontal axis.

1           60.     (Previously Presented) The apparatus of Claim 59 wherein the display support  
2 assembly is cantilevered away from the mounting structure in a generally horizontal  
3 orientation.

1           61.     (Previously Presented) The apparatus of Claim 58 wherein the first axis is a  
2 vertical axis and the second axis is a horizontal axis and the third axis is a horizontal axis  
3 transverse to the second axis.

1           62.     (Previously Presented) The apparatus of Claim 58 wherein the display support  
2 assembly is generally parallel to the second axis and the third axis.

1           63.   (Previously Presented) The apparatus of Claim 58 wherein the display support  
2   assembly is movable in a first plane parallel to a second plane defined by the second axis and  
3   the third axis.